

COMMERCIAL TYPE – **ELECTRICALLY HEATED** AIR CURTAINS
100 mm cross flow fan



KEH - 18



For use in :

- **Small Shops**
- **Bars**
- **Cafeterias**
- **Small Hotels**
- **Banks**
- **Schools**
- **Super markets**



COMMERCIAL TYPE – ELECTRICALLY HEATED AIR CURTAINS
100 mm cross flow fan




Air Curtain KEH – 18 is capable of covering openings of 2.00 m long

Technical Details


Max Door Height (m)	2.3
Max Door Width (m)	2.00
Outlet Velocity (m/sec)	9/8/7
Air Volume (m ³ /h)	2303/2047/1791
Motor Power (W)	240
Capacitor (µF)	4
Motor Speed (rpm)	1310/1200/1000
Power Supply	400V, 3N, 50Hz
Noise level in 1 m (dB)	59/ 55 / 52
Max CURRENT CONS	18 A / Phase
THERMAL POWER (KW)	12 or 15
Toutlet-Tinlet (at 3 speeds)	16 ⁰ C/18 ⁰ C/21 ⁰ C

AIR VELOCITY DISTRIBUTION CHART



Dimensions

A: Total Length	2009±1 (mm)
B: Total Width	274 (mm)
C: Height	172 (mm)
D: Outlet Length	1960 (mm)
E: Outlet Width (int.)	40 (mm)
K: Outlet width (ext.)	54 (mm)
H: Outlet Height	64 (mm)
Weight	37 (Kgr)



OPERATIONAL CHOICES

A) Wired Remote Control Operation

Wall Mounted Wired Remote Control
(from 2.5m up to 6 m cable)
which additionally can be supplied
with an Infrared Remote Control as well .



B) Infrared Remote Control Operation

Unit is provided with a build in Panel
(electronic) and an infrared Remote Control.



**Both above describes options
can be either delivered :**

- 1). Two speed operation (HI - LOW)
- 2). NL operation :
 - 15 different speeds
 - 1 up to 240 units in parallel connection
 - Master - Slave Operation
 - OLEFINI BMS monitoring

